

XSO/E-2236

DENSONS HEAT SHRINKABLE TERMINATIONS UPTO 36 kV For 3 Core XLPE/EPR Insulated Cable



In conformance with IEEE-48,
VDE 0278 & IS: 13573.

Specifications

TEST	TYPE XSO/E - 2236
A.C. Dry withstand Voltage	75 kV / 1 min
Impulse withstand Voltage	170 kV / 10 shots
Corona extinction Voltage	More than 38 kV

Ordering Information

CABLE SIZE (Sq. mm)	FOR 22 kV INDOOR (Kit Code)
3 x 16 - 50	XSE - 21 Enquiry
3 x 70 - 120	XSE - 22 Enquiry
3 x 150 - 225	XSE - 23 Enquiry
3 x 240 - 400	XSE - 24 Enquiry

CABLE SIZE (Sq. mm)	FOR 22 kV OUTDOOR (Kit Code)
3 x 16 - 50	XSO - 21 Enquiry
3 x 70 - 120	XSO - 22 Enquiry
3 x 150 - 225	XSO - 23 Enquiry
3 x 240 - 400	XSO - 24 Enquiry

CABLE SIZE (Sq. mm)	FOR 33 kV INDOOR (Kit Code)
3 x 25 - 50	XSE - 31 Enquiry
3 x 70 - 95	XSE - 32 Enquiry
3 x 120 - 185	XSE - 33 Enquiry
3 x 240 - 400	XSE - 34 Enquiry

CABLE SIZE (Sq. mm)	FOR 33 kV OUTDOOR (Kit Code)
3 x 25 - 50	XSO - 31 Enquiry
3 x 70 - 95	XSO - 32 Enquiry
3 x 120 - 185	XSO - 33 Enquiry
3 x 240 - 400	XSO - 34 Enquiry