

XS OS/ES-2236

DENSONS HEAT SHRINKABLE TERMINATIONS UPTO 36 kV For Single Core XLPE/EPR Insulated Cable



In conformance with IEEE-48,
VDE 0278 & IS: 13573

Specifications

TEST	TYPE XSO/E - 2236
A.C. Dry withstand Voltage	75 kV / 1min
Impulse withstand Voltage	170 kV / 10 shots
Corona extinction Voltage	More than 38 kV

Ordering Information

CABLE SIZE (Sq. mm)	FOR 22 kV INDOOR (Kit Code)	
1 x 16 - 50	XSES - 21	Enquiry
1 x 70 - 150	XSES - 22	Enquiry
1 x 185 - 300	XSES - 23	Enquiry
1 x 400 - 630	XSES - 24	Enquiry
1 x 800 - 1000	XSES - 25	Enquiry

CABLE SIZE (Sq. mm)	FOR 22 kV OUTDOOR (Kit Code)	
1 x 16 - 50	XSOS - 21	Enquiry
1 x 70 - 150	XSOS - 22	Enquiry
1 x 185 - 300	XSOS - 23	Enquiry
1 x 400 - 630	XSOS - 24	Enquiry
1 x 800 - 1000	XSOS - 25	Enquiry

CABLE SIZE (Sq. mm)	FOR 33 kV INDOOR (Kit Code)	
1 x 25 - 50	XSES - 31	Enquiry
1 x 70 - 185	XSES - 32	Enquiry
1 x 240 - 400	XSES - 33	Enquiry
1 x 500 - 800	XSES - 34	Enquiry
1 x 1000	XSES - 35	Enquiry

CABLE SIZE (Sq. mm)	FOR 33 kV OUTDOOR (Kit Code)	
1 x 25 - 50	XSOS - 31	Enquiry
1 x 70 - 185	XSOS - 32	Enquiry
1 x 240 - 400	XSOS - 33	Enquiry
1 x 500 - 800	XSOS - 34	Enquiry
1 x 1000	XSOS - 35	Enquiry