

Digital Clamp Meters
Digital Earth Testers
Digital Multimeters
High Voltage Detector
Insulation Testers
Micro Ohm Meters



Digital Earth Tester **DET-20**

FEATURES

- 3½ digit LCD display with Max Reading 1999.
- Earth Resistance Ranges of 0.01Ω to 1999Ω .
- Rechargeable Internal Ni-MH Battery.
- 4 Wire Soil Resistivity Measurement.
- Measurement Method - 3 terminal & 4 terminal.
- Type tested as per IS-9223.



GENERAL SPECIFICATIONS

- **Earth Resistance Ranges**
0.01 Ω To 19.99 Ω
0.1 Ω To 199.9 Ω
1 Ω To 1999 Ω
- **Accuracy (25° C ± 5° C)**
± 1.5% of reading ±5 digits valid from 10% of reading to 95% of the range.
- **Test Frequency** : 128 Hz ±0.5 Hz
- **Test Current**
20 - Ohm Range : 10 mA AC rms
200 - Ohm Range : 1 mA AC rms
2000 - Ohm Ranges : 100 μA AC rms
Test current is generally constant throughout the range.
- **Earth Voltage Range** : 0 - 200VAC , **Resolution** : 0.1V, **Accuracy** : 2% of Range.
- **Interference**
Interference voltages of 20 V ± 5% peak-to-peak, 50 Hz in the potential circuit will have a maximum effect of ± 1% on the reading obtained for the 20 Ω to 2 k Ω ranges.
- **Minimum Open Circuit Output Voltage** : 36 V Approx.
- **Display** : 3½ digits LCD, max. Reading 1999
- **Influence of Temperature** :
< ± 0.2% per °C over the temperature range 0-20°C and 28-55 °C.
- **Temperature Range:**
Operating : 0°C to +55°C
Storage : - 20°C to +70°C
- **Humidity**
Operating : 95% RH non condensing max. at 40°C
Storage : 93% RH max. at 55°C
Flash Test : 3 kV AC.
- **Voltage Withstand**
In the event of a system fault, the instrument will withstand 240V AC, applied between any two terminals.
- **Dimensions** : Approx. 180 (H) x 100 (W) x 54 (D)mm.
- **Weight** : Approx. 550gms.
- **Power supply** : Internal, rechargeable Ni-MH 1.2V, 600mAh x 8 Nos.
- **Charging time** : Recommended 16hrs.
- **Single Charge Battery Life** : Approximately 5 - 6 hrs of continuous operation on mid ranges.

STANDARD ACCESSORIES

1. Operating Instruction Manual
2. Battery Charger.

OPTIONAL ACCESSORIES

- Carrying bag containing
- a. Four spikes of 10 mm dia, 450 mm. long.
 - b. 10 m, 20 m, 30 m & 40 m of cable on a winder as standard.
 - c. Hammer

NOTES

1. The Instrument is accompanied with Test & calibration sheet. 2. Test Facilities can be provided at the factory with the available test set-ups only. 3. The Company's policy is continuous improvement of its products. we therefore reserve the Right of any deviation from illustration or specifications without notice. 4. Stated accuracies are valid from 1/10th of range to FS. 5. Accuracy Specified for temperature range of 25°C ± 5°C & 55%RH ± 10%.

- 4 Wire Soil Resistivity Measurement.
- Measurement Method - 3 terminal & 4 terminal.
- Type tested as per IS-9223.
- Earth Voltage Measurement up to 200V.



we have a solution.....

*Rev. 08/08/01

APPLICATIONS

- Outdoor Earth Testing.
- Substations.
- Captive Power Plants.
- Soil Resistivity for new Installations and many more applications.



The Motwane Manufacturing Company Pvt. Ltd.



REGD. OFFICE & FACTORY : Gyan Baug, Nashik Road, Nashik - 422 101. Tel.: 91 - 253 - 2463752 / 53. Fax : 91 - 253 - 2463197 e-mail: sales@motwane.com

MUMBAI : 434 A, Gyan Ghar, 14th Road, Khar (W) Mumbai- 400 052. Tel.: 91 - 22 - 26058895 / 96 / 97 Fax : 91 - 22 -26058898 e-mail : mumbai@motwane.com

DELHI : 2 D, 2nd Floor, Vandana Building, 11, Tolstoy Marg, Cannaught Place, New Delhi-110 001.
Tel.: 011 - 41522 105. Telefax : 011 - 41522106. e-mail : delhi@motwane.com

BANGALORE : # 8/12, 3rd Floor, Honnam Complex, South Cross Road, Basavanagudi, Bangalore-560004.
Tel. : 080 - 26621186 / 26611323

For an online quotation please visit
www.motwane.com and click
'GET A QUOTE'.

